Model BK - 050



CE

TR Standart Özellikler

» Çelik boru kapasitesi 60 x 3 mm
» Kolay tek dokunuşla kontrol, herhangi bir operatörün bükülme açısını programlamasına ve otomatik olarak kaydetmesine olanak tanır
» Çifthız
» Kontrol panelinden veya dahili ayak pedalından bükme döngüsünü başlatın
» Kolay taşınır tekerlekli, kulplu dolap üstünde tasarlanmıştır.

EN Standard Features

» Mild steel tube capacity 60 x 3 mm
» Easy one touch control allows any operator to program and automatically store bend angle
» Double bending speed
» Bend from the control panel or included foot pedal
» Easy carriage with rollers and handle, compact design

1 Set of Tooling included as Standard
1 takım Boru Kalıbı ile Standart

Dokunmatik Ekran NC (PLC) Kontrollü 10 satırlık 20 programa kadar Kolay izlenebilen büküm İmkanı sağlayan gelişmiş arabirim
Touchscreen that enables to write 10 lines for each 20 different programs with NC (PLC) Digital Controller modern Interface



TR	EN		BK - 050
Min - Maks. Boru Çapı	Min - Max Tube Capacity	mm	Ø 10-60 (1/8"-2")
Maks. Radyus	Max Radius	mm	200
Motor Gücü	Motor Power	kw	2,2
Ölçüler UxGxY	Dimensions LxWxH	mm	750x550x1100
Ağırlık	Weight	kg	140







MALZEME	MATERIAL		BK-050 Maksimum / Maximum
Kalın Etli Boru	Gas Pipe		2" x3,91
Dikişli Boru	Steel Pipe		60x3
Paslanmaz AISI 304-318	Stainless Steel AISI 304-318		60x2
Alüminyum & Sert Bakır	Hard Copper & Aluminium		64x4
Dolu Yuvarlak	Solid Bar		35
Dolu Kare	Solid Rectangle Bar		10x60
Silme Lama Kılıçlama	Flatbar Hardway		60x16
Silme Lama Kolayına	Flatbar Easyway		60x30
Kutu Profil	Box Section		60x30x4